## **EUROPEAN PATENT OFFICE**

## **Patent Abstracts of Japan**

PUBLICATION NUMBER

61167854

PUBLICATION DATE

29-07-86

APPLICATION DATE

21-01-85

APPLICATION NUMBER

60009682

APPLICANT: MURATA MFG CO LTD;


INVENTOR: KUMADA AKIRA;

INT.CL.

: G01N 27/46

TITLE

LIQUID SENSOR



ABSTRACT: PURPOSE: To eliminate the need for having a power source device on the outside or in the outside and to obtain a liquid sensor which is small in size, inexpensive and is suitable for a throw-away application by constituting a primary battery of plural electrodes consisting of different materials and electrolyte in a detecting part.

> CONSTITUTION: The comb-shaped electrodes 2, 3 which constitute a positive electrode and negative electrode are formed of the different materials on a substrate 1. The electrodes 2, 3 are formed of, for example, carbon for the positive electrode 2 and Ni for the negative electrode 3. A water absorbent 5 consisting of, for example, PVA powder and starch is formed like a film onto the substrate 1 contg. the electrodes 2, 3. The electrolyte such as NH<sub>4</sub>Cl and depolarizer such as MnO<sub>2</sub> are mixed with the absorbent 5. The primary battery is thereby constituted of the electrodes 2, 3 and the detecting part consisting of the absorbent 5 which is a mixture composed of the electrolyte and depolarizer. The primary battery functions when water or urine is adsorbed to the absorbent 5. Then the electrolytic NH<sub>4</sub>Cl induces an ionization reaction and the current flows between the electrodes 2 and 3. The detection circuit is driven by the electromotive force thereof.

COPYRIGHT: (C)1986,JPO&Japio